

## PRO MIX MEGA



### Product Description

PRO MIX MEGA is a fine, ready-mix jointing finish and wall finishing for internal use. Air drying. Suitable for a wide variation of backgrounds as e.g. plasterboards, plaster and concrete.

### Advantages

PRO MIX MEGA is a high quality finishing, easy to apply, easy to sand, excellent bond, good crack resistance.

### Application

PRO MIX MEGA can be used directly from the bucket or with some mixing before use. Clean water could be added if it's necessary. Excessive dilution increases shrinkage and retards drying. Add water in increments to avoid over-thinning. It is recommended that not more than 1.0 litre be added per 25kg bucket. If liquid and compound have separated, remix before use. Apply to plasterboard joint a thin layer of compound and embed a paper tape. Remove excess compound and cover tape with a thin layer. Apply second and third coats. Allow each coat to dry thoroughly before applying the next one. Allow to dry thoroughly before final sanding.

For sanding it is recommended to use a 220 paper when manual and a 120 with a machine. A primer (Ri-

Kombigrund) is recommended prior to a wallpaper application. PRO MIX MEGA can be used by hand, with Tape Tools and by Air-less application. Application thickness is up to about 2mm.

The drying time (overnight) depends on climatic conditions. Do not mix with other materials. Cleaning with clean water.

### Site Conditions

Air-, material and background temperature have to be above +8°C. The background has to be solid, clean, dust free and dry.

### Handling

Q1: Fill the joints and deduct excessive material from surface. Bed Rigips paper tape into the joint and cover it with additional material.  
 Q2: If necessary remove excessive material from joints. Once material set, cover the existing joint with additional material. This is necessary as long as any transitions exist. Once the material dried, sand it if necessary.  
 Q3: Cover full surface by thin strength of coating and that followed remove material to close the pores.  
 Q4: Cover full surface with up to 2mm strength of coating.

### Quality Standard

Q1 – Q4

### EN-Classification

 3A – EN 13963 – A1 – NPD

### Product Data

<b>Application-thickness</b>	up to 2 mm
<b>Working-time</b>	max. 3 months
<b>Drying time</b>	app. 18 hours
<b>Consumption</b>	<u>Vario-Joint:</u> app. 400g/m <sup>2</sup>
	<u>AK-Joint:</u> app. 300g/m <sup>2</sup>
	<u>Joint-Surface:</u> app. 80g/m <sup>2</sup>
	<u>Surface:</u> app. 1,7 kg/m <sup>2</sup> /mm
<b>Fire resistance</b>	A1

### Information

<b>Package-size</b>	0,5 kg / 1 kg / 5 kg / 15 kg / 25 kg
<b>Storage</b>	Shelf life: Ensure stock rotation and use within 12 months of the marked date. Protect from freezing - store between 2°C and 30°C

For further information please contact

Saint-Gobain Rigips Austria GesmbH  
 Wiener Neustädter Straße 63  
 A-2734 Puchberg / Schneeberg

Tel. +43 (0) 2636 / 2203-0  
 Fax +43 (0) 2636 / 2206-625

[www.rigips.com](http://www.rigips.com)



Handling



Working time



Application thickness



Consumption



Quality standard

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.