

# **ProMix Filler**





# **ProMix Filler**



# **Technical Data**

EN-Classification	1A - EN 13963 - A1 - NPD
Application thickness	0 – 20 mm
Consumption	ca. 350 g/m²
Fire resistance	A1
Package size	25 kg
Storage	Use within 12 months of the production date on packaging. Protect from freezing - store between +5°C and +30°C.

### **Product Description**

**ProMix FILLER** is a fine, manual ready-mix jointing compound for internal use. Air drying material, suitable for filling the joints for first / concealed plasterboard layers in multi-planked gypsum board constructions.

#### **Advantages**

**ProMix FILLER** has a long workability, is always ready to use and is particularly smooth.

# Site Conditions

Air, material and surface temperature have to be above  $+5^{\circ}$ C and should be below  $+30^{\circ}$ C. The background must be solid, clean, dry, frost- and dust-free.

### Application

**ProMix FILLER** is ready-mixed in the bucket and can be used immediately. The filler hardens in the air by drying out.

**ProMix FILLER** is only intended for concealed board layers in multi-planked gypsum board constructions. Drying times depend on climatic conditions. Do not mix with other materials.

- Fill joints and remove flush with the surface.
- After drying, fill the joints again and flush with the surface. Repeat this process until the joints are filled (in the dried state)
- Only after the ProMix Filler has dried you should start installing the next layer of plasterboards
- Do not use below + 5°C and above + 30°C (permanent) room and plasterboard temperature
- Clean tools with clean water

## **EN-Classification**





Wien - 07/2021