

Rigips RIMANO Glet XL



Product Description

RIMANO GLET XL is a fine smoothing plaster, based on gypsum for finishing of walls and ceilings.

Components: fine gypsum, additives for improvement of application and adhesion.

Advantages

RIMANO GLET XL is an off-white and fine product and therefore ideal as a background for paints. RIMANO GLET XL has a prolonged setting time of approximately 90min.

The special additives inside ensure an easy and fast workability on even and uneven backgrounds.

RIMANO GLET XL is possible to be used in one or two layers to finish the wall. If RIMANO GLET XL is used in two layers you can work wet in wet and thus saves time.

Rimano GLET XL is a low consumption product, ensuring high material cost efficiency for projects.

Application

For complete covering of concrete undergrounds together with Rikombi-

Kontakt as bonding agent (low suction background).

Suitable for use on concrete, gas concrete, dry cement or lime plaster and gypsum surfaces. For high suction background use Rikombi-Grund for priming.

RIMANO GLET XL is not suitable for tiling.

Site Conditions

Air-, material and background temperature have to be above +5°C. The background has to be solid, clean, dust free and dry.

Handling

Assure that the substrate is clean and dry and free of moulding oil remainders. Remove any loose particles or coats with low adhesive properties. Add approx 1,5kg RIMANO GLET XL to 1 litre of clean water and leave to stand for around 5 minutes. Then mix either by hand or with an electric drill with mud paddle (low speed) till the mixture is lump-free.

Working in one layer:

Apply RIMANO GLET XL on the wall. Smooth material vertically and horizontally.

Working in two layers:

Apply RIMANO GLET XL on the wall at desired layer thickness. For the first layer please use material in strong consistency. Once the setting time has been reached apply the second layer immediately (wet in wet). For the second layer please use material in soft consistency.

EN-Classification

EN 13279-1- A1- B1/20/2

Product Data

Application-thickness	0 – 2 mm
Working-time	app. 90 min.
Consumption	app. 900g/m ² /mm
Fire resistance	A1
Package-size	12,5 kg / 25 kg
Storage	
Shelf life: Ensure stock rotation and use within 12 months of the marked date. Protect from freezing - store between 2°C and 30°C.	

For further information please contact:

Saint-Gobain Rigips Austria GesmbH
Wiener Neustädter Straße 63
A-2734 Puchberg / Schneeberg

Tel. +43 (0) 2636 / 2203-0
Fax +43 (0) 2636 / 2206-625

www.rigips.com



Handling



Working time



Application thickness



Consumption



Quality standard

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.