

Rigips RIMANO 0-3



Product Description

RIMANO 0-3 is a fine smoothing plaster, based on gypsum for finishing and filling of walls and ceilings.

Components: fine gypsum, additives for improvement of application and adhesion.

Advantages

RIMANO 0-3 is an easy workable product with a smooth surface. RIMANO 0-3 has high adhesion properties. Application thickness can be pulled out up to 0 mm. It is a fine product and therefore great as a background for varnishes, wallpapers and paints.

Application

RIMANO 0-3 is a fine smoothing plaster and especially suitable for the use on concrete elements for closing pores.

For complete covering of concrete undergrounds, dry cement or lime plaster and gypsum surfaces together with Rikombi-Kontakt as bonding agent (low suction background) in indoor areas with common moisture, included for domestic kitchen and bathroom area. For filling cracks, holes and closing joints.

RIMANO 0-3 is not suitable for tiling and jointing of plasterboards.

Site Conditions

Air-, material and background temperature have to be above +5°C. Assure that the substrate is clean and dry and free of moulding oil remainders. Remove any loose particles or coats with low adhesive properties.

Preparation


For high suction background use Rikombi-Grund for priming and for low-suction backgrounds use Rikombi-Kontakt as a bonding agent.

Handling

Add approximately 1,2 kg RIMANO 0-3 into 1 litre of clean water and allow to soak in for around 5 minutes. Then mix either by hand or with an electric drill with mud paddle (low speed) till the mixture is lump-free.

Apply RIMANO 0-3 on the wall in the requested application thickness. The following layers can be only applied after complete drying out.

EN-Classification

 EN 13279-1- A1- B1/20/2

Product Data

Mixing ratio	app. 1,2 kg / 1 L water
Working-time	app. 60 min.
Application-thickness	0 – 3 mm
Consumption	app. 0,9 kg/m ² /mm
Fire resistance	A1
Vapour diffusion resistance	$\mu = 10$
Flexural- and tensile bond strength	According to EN 13279-1
Package-size	2,5 kg / 5 kg / 12,5 kg / 25 kg
Storage	
Shelf life: Ensure stock rotation and use within 12 months of the marked date. Use unsealed bags within 3 months. Protect from freezing - store between +2°C and +30°C.	

For further information please contact:

Saint-Gobain Rigips Austria GesmbH
Wiener Neustädter Straße 63
A-2734 Puchberg / Schneeberg

Tel. +43 (0) 2636 / 2203-0
Fax +43 (0) 2636 / 2206-625

www.rigips.com



Application



Handling



Working time



Application thickness



Consumption

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.